Approvals

Valves | Single Check Valves | Check Valves, Single

Models H84X, H44X, H44X-01 and H44X-1.6

Product Description

Model No	Description	Valve Size		Rated Working Pressure		Remarks
		in	(mm)	psi	(kPa)	
Model H84X	Swing Check Valve, Grooved Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300, 76.1, 139.7, 165.1)	365	(2515)	a, b
Model H44X	Swing Check Valve, Flanged Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	300	(2065)	a, b
Model H44X-01	Swing Check Valve, Flanged Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	300	(2065)	a, b
Model H44X-1.6	Swing Check Valve, Flanged Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	300	(2065)	a, b, c

Remarks:

a. For use in horizontal and vertical installations.

b. Resilient seat.

c. Flanged end connections conform to EN1092-2.

Details

Category Check Valves, Single

Company

- **Shandong Lede Machinery Co. Ltd.**
- No. 3998 West Weihuan N Rd, Weicheng Dist, Weifang City, Shandong 261057,

Approvals

Class of Work	1210 - Single Check Valves
Approval Standard	FM 1210 - Swing Check Valves
Certification Type	FM Approved
Listing Country	China

China

- **http://wflede.com**