FM Approvals

Valves | Water Control Valves (OS&Y and NRS Gate Valves) | Gate Valves, Inside Screw

Model Z45X-03-175, Z45X-04-175

Product Description

Resilient Seated Gate Valves. 2 through 12 inch NPS. Model Z45X-04-175 is available with indicator post flange. Available with the following end connections and rated working pressure:

Product Specification

Model No	Valve Size		Rated Working Pressure		End Connection
	in	(mm)	psi	(kPa)	
Z45X-03-175	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	175	(1205)	Flange x Flange (ANSI)
Z45X-04-175	4, 5, 6, 8, 10, 12	(100, 125, 150, 200, 250, 300)	175	(1205)	Flange x Flange (ANSI)

Details

Category	Gate Valves, Inside Screw
Class of Work	1120 - OS&Y and NRS Gate Valves

Company

- **Shandong Lede Machinery Co. Ltd.**
- No. 3998 West Weihuan N Rd, Weicheng Dist, Weifang City, Shandong 261057, China
- **http://wflede.com**

Approvals

Approval Standard	FM 1120, 1130 - Fire Service Water Control Valves (OS&Y and NRS Type Gate Valves)
Certification Type	FM Approved
Listing Country	China